



## NT-HBSS280 BORING MACHINE HORIZONTAL

NT-HBSS280 BORING MACHINE HORIZONTAL

The NT HBSS-280 is a heavy duty horizontal boring machine. The multiple boring head configuration is adjustable for varying hole layouts for customer flexibility. Rugged cast iron base for a solid footing and decades of performance. Pneumatic hold downs and drill cycle. Ideal for panel, softwood, hardwood and plastic products

MACHINE HP: (2) 2 HP

VOLTAGE, FREQUENCY: 230/460 Volt 60HZ

PHASE: 3 Phase

AMP REQUIREMENT: 6/3 Amps

SPINDLE ARRANGEMENT: (6) Inline Spindles

SPINDLE DIAMETER: 1/2" Chuck

SPINDLE RPM: 4200 RPM

ELEVATION STYLE: Manual Wheel Adjustment

APPROVED ELECTRICAL PARTS: CE Approved Parts

DUAL VOLTAGE MOTORS: 230/460 Volt

CONTROL VOLTAGE: 24 Volt

ADJUSTABLE OPERATOR PANEL: Movable Pedestal

MAX. WORKING LENGTH: 90"

MAX. WORKING THICKNESS: 4-1/2"

HOLD DOWN STYLE: Pneumatic Clamps

**Log in to view more.**

---

Categories: [Boring](#), [Horizontal Drills](#), [Machines](#)

# YOU MUST BE LOGGED IN TO VIEW ADDITIONAL INFORMATION.

Email

Password

[Forgot Password?](#)

Remember Me