



NT-N4230 MOULDER 4 HEAD

NT-N4230 MOULDER 4 HEAD

The NT N4230 is our standard 4 head N series machine. The 6" x 9" capacity moulder with a standard 4 head configuration provides excellent S4S and simple profiled mouldings. Features such as chrome table, Siko mechanical readouts, automatic bed oiler and independent motors powering 1-13/16" 6000RPM spindles are standard. There are a vast amount of optional features available making the N series is an excellent option to higher priced competitive models.

MACHINE HP: 43 HP

VOLTAGE, FREQUENCY: 230/460 Volt 60HZ

PHASE: 3 Phase

AMP REQUIREMENT: 228/114 Amps

CONFIGURATION: B-R-L-T

1ST SPINDLE: Bottom Horizontal 10HP 6,000RPM

2nd SPINDLE: Right Vertical 10HP 6,000RPM

3rd SPINDLE: Left Vertical 10HP 6,000RPM

4th SPINDLE: Top Horizontal 15HP 6,000RPM

SPINDLE DIAMETER: 1-13/16"

SPINDLE RPM: 6000 RPM

UNDER THE NUT CAPACITY: Horizontal 10" Vertical 7"

FEED HP: 7.5 HP

FEED SYSTEM: Knurled and Urethane Rollers

DRIVE SYSTEM: Carden Shaft

Log in to view more.

Categories: [Machines](#), [Moulders](#), [Profiling](#)

YOU MUST BE LOGGED IN TO VIEW ADDITIONAL INFORMATION.

Email

Password

[Forgot Password?](#)

Remember Me